

Model	Ausführung	Rahmen- höhe C-T (cm)	horizontale Oberrohr- länge (mm)	Steuerrohr- höhe (mm)	Oberrohr direkt (mm)	Sitz- winkel	Lenk- winkel	Nachlauf (mm)	Tretlager- höhe (mm)	Rad- stand (mm)	Hinterbau- länge (mm)	Überstands- höhe (mm)	max. Reifen- breite	Steuer- satzmaß	Rohrsatz	
Loschwitz	Diamant	50	575	603	555	72,5	72,5	52	286	1052	445	776	42-622	1 1/8 A-Head	P&P 25CrMo4	
		53	586	603	573	72,5	72,5	52	286	1064	445	791	42-622			
		56	597	633	584	72,4	72,4	52	286	1075	445	819	42-622			
		60	609	663	598	72,4	72,4	53	286	1087	445	853	42-622			
		63	621	693	610	72,4	72,4	53	286	1100	445	882	42-622			
	Trapez	47	563	603	539	72,4	72,4	52	286	1040	445	537	42-622	1 1/8 A-Head	P&P 25CrMo4	
		50	575	603	555	72,5	72,5	52	286	1052	445	555	42-622			
		53	585	633	566	72,5	72,5	52	286	1063	445	574	42-622			
		57	597	663	580	72,4	72,4	52	286	1075	445	594	42-622			
		60	610	693	592	72,4	72,4	53	286	1088	445	613	42-622			
Borsberg	Diamant	50	574	580	560	72,0	72,0	54	290	1053	440	785	50-599	1 1/8 A-Head	Columbus Zona	
		54	590	610	578	72,0	72,0	54	290	1068	440	817	50-599			
		58	605	640	595	72,0	72,0	54	290	1083	440	850	50-599			
		62	620	670	612	72,0	72,0	54	290	1098	440	884	50-599			
	Curve	40	522	536	500	72,0	71,0	54	272	994	425	454	47-599	1 1/8 A-Head	P&P 25CrMo4	
		44	534	566	512	72,0	71,0	54	272	1006	425	480	47-599			
Löbtau	Diamant	50	544	599	526	72,0	72,0	53	280	1018	440	767	40-622	1 1/8 A-Head	Dedacciai double butted	
		53	560	619	543	72,0	72,0	53	280	1034	440	791	40-623			
		56	574	639	560	72,0	72,0	53	280	1048	440	815	40-624			
		59	590	659	577	72,0	72,0	53	280	1063	440	839	40-625			
		62	605	679	595	72,0	72,0	53	280	1078	440	863	40-626			
Klotzsche	Diamant	50	565	561	548	74,0	74,0	51	284	1008	425	758	28-622	1" A-Head	Mannesmann 25CrMo4	
		53	577	571	564	74,0	74,0	51	284	1020	425	777	28-622			
		56	590	591	580	74,0	74,0	51	284	1033	425	801	28-622			
		59	603	611	594	74,0	74,0	51	284	1045	425	825	28-622			
		62	616	632	609	74,0	74,0	51	284	1057	425	849	28-622			
Weißer Hirsch	Diamant	50	543	550	529	73,7	73,7	51	279	967	405	761	28-622	1" A-Head	Dedacciai double butted	
		52	552	560	540	73,7	73,7	51	279	976	405	776	28-622			
		54	560	575	549	73,7	73,7	51	279	983	405	793	28-622			
		56	570	590	559	73,7	73,7	51	279	992	405	809	28-622			
		58	577	605	568	73,7	73,7	51	279	999	405	826	28-622			
		60	586	621	577	73,7	73,7	51	279	1007	405	843	28-622			
Johannstadt	Diamant	50	600	630	600	67,0	65,0	120	315	1150	460	775	50-622	1" Gewinde	CrMO	
		55	620	645	620	67,0	65,0	120	315	1160	470	825	50-622			
		57	630	650	630	67,0	65,0	120	315	1160	470	845	50-622			
		Schwanhals	50	640	675	605	67,0	65,0	120	300	1160	470	470	50-622		
			53	650	680	610	67,0	65,0	120	300	1160	470	470	50-622		
Striesen	Diamant	50	575	603	555	72,5	72,5	52	286	1052	445	776	42-622	1 1/8 A-Head	P&P 25CrMo4	
		53	586	603	573	72,5	72,5	52	286	1064	445	791	42-622			
		56	597	633	584	72,4	72,4	52	286	1075	445	819	42-622			
		60	609	663	598	72,4	72,4	53	286	1087	445	853	42-622			
		63	621	693	610	72,4	72,4	53	286	1100	445	882	42-622			
		Trapez	47	563	603	539	72,4	72,4	52	286	1040	445	537	42-622	1 1/8 A-Head	P&P 25CrMo4
			50	575	603	555	72,5	72,5	52	286	1052	445	555	42-622		
			53	585	633	566	72,5	72,5	52	286	1063	445	574	42-622		
			57	597	663	580	72,4	72,4	52	286	1075	445	594	42-622		
			60	610	693	592	72,4	72,4	53	286	1088	445	613	42-622		